

HELIAX® Discrete MULTIMODE FIBER JUMPER LSZH NBOOT



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Wireless Fiber Cable Assemblies
Product Brand	HELIAX®
Product Series	FJ
Ordering Note	ANDREW® non-standard product

General Specifications

Color, connector A	Aqua
Color, connector B	Aqua
Construction Type	Discrete fiber tail
Interface, Connector A	DLC
Interface Feature, connector A	Standard
Interface Body Style, connector A	Straight
Interface, Connector B	DLC
Interface Feature, connector B	Outdoor
Interface Body Style, connector B	Straight
Jacket Color	Black
Total Fibers, quantity	2

Dimensions

Cable Assembly Length Range (m)	1 – 50
Diameter Over Jacket	5 mm 0.197 in

Mechanical Specifications

Minimum Bend Radius	20 mm 0.787 in
---------------------	------------------

Optical Specifications

FJ-02TAADDB

Fiber Mode	Multimode
Fiber Type	OM4, bend insensitive
Insertion Loss, typical note	Insertion loss is measured at 850 nm
Insertion Loss, typical	0.5 dB

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Environmental Space	Outdoor

Packaging and Weights

Cable weight	20 kg/km 13.439 lb/kft
--------------	--------------------------

* Footnotes

Insertion Loss, typical note	Insertion loss is measured at a room temp of +20°C (+68°F)
------------------------------	--