


# R8CLAMP-CNL-E3B



KwikClamp™ Hanger for RG8 cable, triple stack, C-Channel compatible; includes hardware

## Product Classification

<b>Product Type</b>	Hanger kit
<b>Product Brand</b>	KwikClamp™
<b>Ordering Note</b>	ANDREW® standard product in Europe, the Middle East, and Africa   Minimum order quantity (MOQ) is 1 box

## General Specifications

<b>Cables per Hanger</b>	3
<b>Color</b>	Black
<b>Hanger Type</b>	KwikClamp™ hanger
<b>Mounting</b>	Channel section 40 x 22 x 1.5 mm

## Dimensions

<b>Height</b>	165 mm   6.496 in
<b>Width</b>	32 mm   1.26 in
<b>Length</b>	42 mm   1.654 in
<b>Compatible Diameter, maximum</b>	11 mm   0.433 in
<b>Compatible Diameter, minimum</b>	10 mm   0.394 in
<b>Nominal Size</b>	3/8 in
<b>Hanger Spacing, maximum</b>	1.83 m   6.004 ft

## Electrical Specifications

<b>Return Loss Effect, maximum</b>	0.1 dB
<b>DTF Effect, maximum</b>	0.1 dB

## Material Specifications

<b>Material Type</b>	Engineered plastic   Stainless steel
----------------------	--------------------------------------

## Mechanical Specifications

# R8CLAMP-CNL-E3B

---

## Vibration Survival

≥4 hours at resonant frequency

## Environmental Specifications

### Operating Temperature

-40 °C to +70 °C (-40 °F to +158 °F)

### Corrosion Resistance, minimum with no degradation

≥500 hours in salt spray chamber

### Environmental Strength Capability

Five times cable weight

### UV Resistance, minimum with no degradation

≥100 hours exposure in accelerated UV life chamber

## Packaging and Weights

### Height, packed

27 cm | 10.63 in

### Width, packed

21 cm | 8.268 in

### Length, packed

11 cm | 4.331 in

### Included

Hardware

### Packaging quantity

100

### Weight, gross

6.74 kg | 14.859 lb