

L4-CLAMP-E3B



KwikClamp™ Hanger for 1/2 in coaxial cable, triple stack; includes hardware

Product Classification

Product Type	Hanger kit
Product Brand	KwikClamp™
Ordering Note	ANDREW® standard product in Europe, the Middle East, and Africa Minimum order quantity (MOQ) is 1 box

General Specifications

Cables per Hanger	3
Color	Black
Hanger Type	KwikClamp™ hanger
Mounting	3–25 mm angle iron 3–25 mm flat plate Round Member 8–25 mm

Dimensions

Height	170 mm 6.693 in
Width	32 mm 1.26 in
Length	42 mm 1.654 in
Compatible Diameter, maximum	17 mm 0.669 in
Compatible Diameter, minimum	15 mm 0.591 in
Nominal Size	1/2 in
Hanger Spacing, maximum	1.83 m 6.004 ft

Electrical Specifications

Return Loss Effect, maximum	0.1 dB
DTF Effect, maximum	0.1 dB

Material Specifications

Material Type	Engineered plastic Stainless steel
---------------	--------------------------------------

L4-CLAMP-E3B

Mechanical Specifications

Vibration Survival ≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature -40 °C to +70 °C (-40 °F to +158 °F)

Corrosion Resistance, minimum with no degradation ≥500 hours in salt spray chamber

Environmental Strength Capability Five times cable weight

UV Resistance, minimum with no degradation ≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed 25 cm | 9.843 in

Width, packed 30 cm | 11.811 in

Length, packed 30 cm | 11.811 in

Included Hardware

Packaging quantity 100

Weight, gross 10.4 kg | 22.928 lb