
L4A-PNMDM-3M-X



Product Classification

Product Type SureFlex® standard

Product Brand HELIAX® | SureFlex®

Product Series LDF4-50A

General Specifications

Attachment, Connector B Field attachment

Body Style, Connector AStraightBody Style, Connector BStraightInterface, Connector AN Male

Interface, Connector B 7-16 DIN Male

Specification Sheet Revision Level A

Dimensions

Length 3 m | 9.843 ft

Nominal Size 1/2 in

Electrical Specifications

DTF, Connector A -32 dB

Jumper Assembly Sample Label



L4A-PNMDM-3M-X



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency

Classification

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

Included Products

L4TDM-PS – 7-16 DIN Male Positive Stop™ for 1/2 in LDF4-50A cable

L4TDM-PSA 7-16 DIN Male Positive Stop™ for 1/2 in AL4RPV-50, LDF4-50A, HL4RPV-50 cable

LDF4-50A - LDF4-50A, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE

jacket Halogen free jacketing non-fire-retardant (General propose cable for outdoor use only)