

# ATCB-DB9-010



RET control cable with male DB9 which has 4-40 screws and female AISG connector

- Feeds data and power to RET system components
- Directly connects RET actuator with RRH (Remote Radio Heads) with DB9 connector

## Product Classification

**Product Type** AISG DB9 cable

## General Specifications

**AISG Connector A** 8-pin DIN Female

**AISG Connector A Body Style** Straight

**AISG Connector A Standard** IEC 60130-9

**Color** Black

**Connector B** 9-pin D-sub Male

**Data Conductor Type** 0.24 mm<sup>2</sup> (24 AWG) twisted pair

**EU Certification** CB | CE

**Power Conductor Type** 0.82 mm<sup>2</sup> (18 AWG) stranded

## Dimensions

**Length** 10 m | 32.808 ft

**Diameter Over Jacket** 8 mm | 0.315 in

## Electrical Specifications

**Protocol** AISG 1.1 | AISG 2.0

**Voltage, maximum** 300 V

## Environmental Specifications

**Operating Temperature** -40 °C to +70 °C (-40 °F to +158 °F)

**Relative Humidity** Up to 100%

**Climatic Sequence Test Method** IEC 60068-2-14

**Corrosion Test Method** IEC 60068-2-11, Test Condition Ka

**Ingress Protection Test Method** IEC 60529:2001, IP67

# ATCB-DB9-010

---

**UV Resistance Test Method** IEC 60068-2-5, Test Condition B

## Packaging and Weights

**Weight, net** 0.9 kg | 1.984 lb

## Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.andrew.com/ProductCompliance">www.andrew.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant

