L7CLAMP-CNL-1B



KwikClamp™ Hanger for 1-5/8 in coaxial cable, single stack, C-Channel compatible; includes hardware

Product Classification

Product TypeHanger kitProduct BrandKwikClamp™

Ordering Note ANDREW® standard product in Europe, the Middle East, and

Africa | Minimum order quantity (MOQ) is 1 box

General Specifications

Cables per Hanger 1

Color Black

Hanger Type KwikClamp™ hanger

Mounting Channel section 40 x 22 x 1.5 mm

Dimensions

Maximum Stack Height 1

 Height
 152 mm | 5.984 in

 Width
 69 mm | 2.717 in

 Length
 44 mm | 1.732 in

 Compatible Diameter, maximum
 50 mm | 1.969 in

 Compatible Diameter, minimum
 48 mm | 1.89 in

Nominal Size 1-5/8 in

Hanger Spacing, maximum 1.83 m | 6.004 ft

Electrical Specifications

Return Loss Effect, maximum0.1 dBDTF Effect, maximum0.1 dB

Material Specifications

Material Type Engineered plastic | Stainless steel



L7CLAMP-CNL-1B

Mechanical Specifications

Vibration Survival ≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C}$ to $+70 \,^{\circ}\text{C}$ ($-40 \,^{\circ}\text{F}$ to $+158 \,^{\circ}\text{F}$)

Corrosion Resistance, minimum with no degredation ≥500 hours in salt spray chamber

Environmental Strength Capability Five times cable weight

UV Resistance, minimum with no degradation ≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

 Height, packed
 101 cm | 39.764 in

 Width, packed
 71 cm | 27.953 in

Length, packed 81.3 cm | 32.008 in

Included Hardware

Packaging quantity 100

Weight, gross 17 kg | 37.479 lb

* Footnotes

Maximum Stack Height Fiber, Hybrid, Power