

Double Block Hanger for 18 to 20mm Cables - Hardware Sold Separately (search 243095-SERIES-HARDWARE for options available)

Product Classification

Product Type Hanger kit
Product Brand HELIAX®

Ordering Note ANDREW® standard product (Global)

General Specifications

Cables per Hanger 2

Color Black

Hanger Type Double block hanger

Mounting Mounting hole clearance for 3/8, 16 UNC or M10 threaded rod

Dimensions

Maximum Stack Height 4

 Height
 27.9 mm | 1.098 in

 Width
 39.6 mm | 1.559 in

 Length
 72.4 mm | 2.85 in

Compatible Cable Diameter Range 17.8–20.1 mm

Compatible Diameter, maximum20.1 mm0.791 inCompatible Diameter, minimum17.8 mm0.701 in

Nominal Size 5/8 in

Electrical Specifications

Return Loss Effect, maximum 0.1 dB

DTF Effect, maximum 0.1 dB

Material Specifications



Page 1 of 2

BHD-58

Material Type

Engineered plastic

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C}$ to $+85 \,^{\circ}\text{C}$ ($-40 \,^{\circ}\text{F}$ to $+185 \,^{\circ}\text{F}$)

Environmental Strength Capability Double cable weight

UV Resistance, minimum with no degradation ≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

 Height, packed
 3.8 cm | 1.496 in

 Width, packed
 17.8 cm | 7.008 in

 Length, packed
 25.4 cm | 10 in

Packaging quantity 10

Weight, gross 0.45 kg | 0.992 lb

* Footnotes

Maximum Stack Height Fiber, Hybrid, Power