SHK-12-1-P



Single Hanger Kit for 1/2 in coaxial cable, single stack; includes hardware and angle adapter

Product Classification

| Product Type | Hanger kit |
|---------------------------------|--|
| Product Brand | ValuSite™ |
| Ordering Note | ANDREW® non-standard product |
| General Specifications | |
| Cables per Hanger | 1 |
| Color | Black |
| Hanger Type | Composite clamp |
| Mounting | M8 hardware |
| Dimensions | |
| Maximum Stack Height | 1 |
| Height | 25.9 mm 1.02 in |
| Width | 25.9 mm 1.02 in |
| Length | 46.2 mm 1.819 in |
| Compatible Cable Diameter Range | 15.2–16.3 mm |
| Compatible Diameter, maximum | 16.3 mm 0.642 in |
| Compatible Diameter, minimum | 15.2 mm 0.598 in |
| Nominal Size | 1/2 in |
| Electrical Specifications | |
| Return Loss Effect, maximum | 0.1 dB |
| DTF Effect, maximum | 0.1 dB |
| Material Specifications | |
| Material Type | Engineered plastic Stainless steel 304 |

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 2, 2025

SHK-12-1-P

Mechanical Specifications

| Vibration Survival | ≥4 hours at resonant frequency |
|---|--------------------------------------|
| | |
| Environmental Specifications | |
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
| Corrosion Resistance, minimum with no degredation | ≥500 hours in salt spray chamber |
| Environmental Strength Capability | Double cable weight |

≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

UV Resistance, minimum with no degradation

| Height, packed | 30.4 cm 11.969 in |
|--------------------|--------------------------|
| Width, packed | 27.9 cm 10.984 in |
| Length, packed | 2.5 cm 0.984 in |
| Included | Angle adapter Hardware |
| Packaging quantity | 1 |
| Weight, gross | 0.45 kg 0.992 lb |

Regulatory Compliance/Certifications

| Agency | Classification |
|------------|--|
| CHINA-ROHS | Below maximum concentration value |
| REACH-SVHC | Compliant as per SVHC revision on www.andrew.com/ProductCompliance |
| ROHS | Compliant |
| UK-ROHS | Compliant |



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 2, 2025

Page 2 of 2