CLT4HR-5M-CO



MQ Multiport cluster 4 ports cable assembly with interface type MQ female to 4.3-10 male Right angle,size 1/4", length 5 meters

Product Classification

Product Type	Wireless transmission cable assembly
Product Series	MQ
Warranty	Two years
General Specifications	
Attachment, Connector A	Factory attached
Attachment, Connector B	Factory attached
Body Style, Connector A	Straight
Body Style, Connector B	Right angle
Interface, Connector A	MQ Female
Interface, Connector B	4.3-10 Male
Specification Sheet Revision Level	A

Dimensions

Length	5m	16.404 ft
Nominal Size	1/4 in	

Port Configuration

Pin Assignment	Label
1	MQ4-1(R-)
2	MQ4-2(CR-)
3	MQ4-3(CL-)
4	MQ4-4(L-)

VSWR/Return Loss

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 20, 2025

<u>CLT4HR-5M-CO</u>

Frequency Band	VSWR	Return Loss (dB)	Insertion Loss, typical (dB)
0–2700 MHz	1.151	23.1	2.2
2700-4200 MHz	1.25	19.1	3
4200–6000 MHz	1.398	15.6	3.55
Mechanical Specifications			
Minimum Bend Radius, multiple Ben	ds	25.4 mm 1 in	
Minimum Bend Radius, single Bend		25.4 mm 1 in	

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Immersion Test Method	IEC 60529, IP67

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



* Footnotes

Warranty

For more information, please consult our Product Warranty guidelines

Page 2 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 20, 2025