

# SA-1TR



PIM-Guard® Multifunction Adapter that threads into 3/8" & 1/2" bolts & U-bolts or snaps into 3/4" holes. One 3/4" hole for Snap-in style hangers, supporting three stacks for 4-17mm or two stacks for 26-40mm cables

- Snaps into 3/4" holes to provide 1 inch standoff
- Threads into 3/8" & 1/2" bolts & U-bolts to launch hangers
- Snaps between SnapTak hangers to provide 360 degree hanger rotation

## Product Classification

|               |                                   |
|---------------|-----------------------------------|
| Product Type  | Stand-off mount                   |
| Product Brand | PIM-Guard®                        |
| Ordering Note | ANDREW® standard product (Global) |

## General Specifications

|              |   |
|--------------|---|
| Adapter Type | Stand-off adapter                                     |
| Color        | Black   |
| Mounting     | 1/2 in threads   3/4 in through hole   3/8 in threads |

## Dimensions

|        |                     |
|--------|---------------------|
| Height | 25.908 mm   1.02 in |
| Width  | 28.956 mm   1.14 in |
| Length | 0.03 m   0.1 ft     |

## Material Specifications

|               |                    |
|---------------|--------------------|
| Material Type | Engineered plastic |
|---------------|--------------------|

## Mechanical Specifications

|                    |   |
|--------------------|---|
| Maximum Loading    | Triple stack for hangers SSH-47, SSH-710, SSH-1014, SSH-1416, SSH-411, SSH-1117 |
| Vibration Survival | ≥4 hours at resonant frequency  |

## Environmental Specifications

|                                   |                                     |
|-----------------------------------|-------------------------------------|
| Operating Temperature             | -20 °C to +85 °C (-4 °F to +185 °F) |
| Environmental Strength Capability | Double cable weight                 |

# SA-1TR

---

**UV Resistance, minimum with no degradation** ≥1000 hours

## Packaging and Weights

**Height, packed** 17 cm | 6.693 in

**Width, packed** 13 cm | 5.118 in

**Length, packed** 10 cm | 3.937 in

**Packaging quantity** 10

**Weight, gross** 0.15 kg | 0.331 lb

## Regulatory Compliance/Certifications

**Agency**

ISO 9001:2015

**Classification**

Designed, manufactured and/or distributed under this quality management system